



Emergency Driver Compatibility Guide

Category	Product Series	Series Name	Emergency Driver		
			Factory Installed EM (Internal)	Field Installed EM (Remote Mount)	
LED Linear and Suspension Light	LS100	LED Linear Strip	BLD-CM20E-480800-8W*	BLD-HM15D-YYY	Wiring 1 or 2
	LW139	LED Slim Wrap (4"x4")	BLD-CM20E-480800-8W*	BLD-HM15D-YYY	Wiring 1 or 2
	LW102	LED Wraparound	BLD-CM20E-480800-8W*	BLD-HM15D-YYY	Wiring 1 or 2
	LSP Non-Dimmable	LED Shop Light (Non-Dlm)	-	-	-
	LSP Dimmable	LED Shop Light	-	BLD-HM15D-YYY	Wiring 1 or 2
	INT	LED Integrated Tube	-	-	-
	LUD	LED Suspended up and down	-	BLD-HM15D-YYY	Wiring 1 or 2
LED Waterproof Linear	LV401	LED Tri-Proof Linear	-	-	-
	VT	LED Vapor Tight	-	-	-
LED Panel and Troffer Fixtures	PB	LED Backlit Panel	-	BLD-HM15D-YYY	Wiring 1 or 2
	PE	LED Frame Light	-	BLD-HM15D-YYY	Wiring 1 or 2
	TRCB	LED Center Basket Troffer	BLD-CM20E-480800-8W*	BLD-HM15D-YYY	Wiring 1 or 2
	TR254	TR254 Troffer	-	BLD-HM15D-YYY	Wiring 1 or 2
LED High Bay	UFO (Less Than 150W)	UFO High Bay	-	BLD-HM15D-YYY	Wiring 1 or 2
	UFO (150W-250W)	UFO High Bay	-	BLD-HM25D-YYY	Wiring 1 or 2
	LHB2 (Less Than 165W)	LED Linear High Bay	-	BLD-HM15D-YYY	Wiring 1 or 2
	LHB2 (165W-250W)	LED Linear High Bay	-	BLD-HM25D-YYY	Wiring 1 or 2
LED Recessed Downlight	SDL	LED Slim Downlight (3"/4"/6")	-	BLD-HM15D-YYY	Wiring 3
		LED Slim Downlight (8")	-	BLD-HM15D-YYY	Wiring 1 or 2
	USDL	LED Ultra Slim Downlight	-	BLD-HM15D-YYY	Wiring 3
	UADL	LED Gimbal Downlight	-	BLD-HM15D-YYY	Wiring 3
LED Surface Mount	SMD (Less than 15W)	LED Surface Mount Downlight	-	BLD-HM15D-YYY	Wiring 3
	SMD (15W-25W)	LED Surface Mount Downlight	-	BLD-HM25D-YYY	Wiring 3
	DSK	LED Disk Light	-	BLD-HM15D-YYY	Wiring 3
	DR	LED Double Ring Ceiling Light	Pre-installed Only		

*Internal emergency driver is recommended when it's compatible